

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1 through 28. (Canceled)

29. (New) A method of manufacturing a gear comprising:

providing a die assembly having an upper die, a lower die and a mandrel, one of the upper die and the lower die defining a plurality of gear teeth, the upper and lower dies forming a closed die that defines a die cavity, the mandrel being received into the die cavity;

providing an insert portion formed of a solid substantially void-free metal, the insert portion having a hollow body and a flange, the hollow body having an interior surface, the flange extending circumferentially about the hollow body;

positioning the insert portion onto the mandrel such that at least a portion of the mating splines matingly engage the splines formed on the mandrel;

positioning a preform portion within the die cavity such that the preform portion extends circumferentially about at least a portion of the insert portion, the preform portion being formed of a solid substantially void-free metal;

pressing the preform portion between the upper and lower dies in a pressing direction to form a plurality of gear teeth on the preform portion in single stroke, the preform deforming in at least one axial direction, a radially inward direction and a radially outward direction during the single stroke such that the preform portion is deformed about the opposite axial sides of the flange so as to be fixedly engaged to the insert portion.

30. (New) The method of Claim 29, wherein the preform portion is heated prior to pressing the preform portion between the upper and lower dies.

31. (New) The method of Claim 29, wherein a material is placed between the insert portion and the preform portion prior to the pressing the preform portion between the upper and lower dies, the material being configured to bond the insert portion to the preform portion.

32. (New) The method of Claim 31, wherein the material is selected from a group consisting of brazing materials and soldering materials.

33. (New) The method of Claim 29, wherein the mandrel includes a splined portion that matingly engages an internal spline formed on the interior surface of the hollow body.

34. (New) The method of Claim 29, wherein at least one locking feature is formed on the insert portion, the locking feature being formed such that the preform portion moves radially inward the at least one locking feature when the preform portion is pressed between the upper and lower dies to thereby inhibit radial movement of the insert portion relative to the preform portion.

35. (New) The method of Claim 34, wherein the at least one locking feature is formed on the flange.

36. (New) The method of Claim 35, wherein the at least one locking feature includes a plurality of scallops.

37. (New) The method of Claim 29, wherein the flange includes a first axial side that is generally transverse to a longitudinal axis of the insert portion, and second axial side that is opposite the first side, the second axial side tapering relative to the first axial side such that a radially outward side of the flange is thinner than a radially inward side of the flange.